



HIKVISION
accessories

Controler for 2 readers

DS-K2601T

FUNCTIONS

| | |
|-----------------|------------|
| General | Sí |
| Patrol | Sí |
| Duress | Sí |
| Open door alarm | Sí |
| Antipassback | Sí |
| Puerta Forzada | Sí |
| Tamper | Yes |

INPUTS/OUTPUTS

| | |
|----------------|----------|
| Alarm input | 4 |
| Door sensor | 1 |
| Exit button | 1 |
| Blocking entry | 1 |
| Alarm output | 2 |
| Reader | 2 |

GENERAL INFORMATION

| | |
|-------------------|---------------|
| Serie | Hika-P |
| Número de Puertas | 1 |

COMMUNICATION

| | |
|----------------------------------|--------------------------------|
| Communication mode to the reader | Wiegand 26 / 34 / RS485 |
| PC communication mode | RJ45 (10 / 100M) |

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

| | |
|----------------|----------------|
| Main processor | 32 bits |
| Memory | 32M |

POWER CONSUMPTION

| | |
|-----------------|---------------|
| Power mode | DC |
| Voltage | 12V |
| Consumption (w) | 50W |
| Amperage | 1000mA |

AMBIENT

| | |
|-----------------------|-----------------------|
| Operating temperature | -20 °C ~ 50 °C |
| Use | Indoor |
| Maximum humidity | 90% |

MATERIAL AND DIMENSIONS

| | |
|------------|--------------------------|
| Dimensions | 373 x 345 x 98 mm |
| Net weight | 4700 g |

CAPACITY

| | |
|----------|---------------|
| Cards | 100000 |
| Register | 300000 |

