



## VANDERBILT

### 2-door spc expansion module

SPCA210.100

#### MATERIAL AND DIMENSIONS

|                       |                   |
|-----------------------|-------------------|
| Installation          | Surface           |
| Dimensions            | 200 x 153 x 47 mm |
| Material              | ABS plastic       |
| Net weight            | 360 g             |
| Weight with packaging | 540 g             |

#### POWER CONSUMPTION

|            |            |
|------------|------------|
| Power mode | DC         |
| Voltage    | 9.5V ~ 14V |
| Amperage   | 80mA       |

#### TECHNICAL CHARACTERISTICS

|                            |     |
|----------------------------|-----|
| Box tamper                 | Si  |
| Armed / disarmed indicator | Si  |
| LED indicator              | Yes |

#### ZONES

|                      |                       |
|----------------------|-----------------------|
| Wired on-board zones | 4                     |
| RFL settings         | 4K7 / 4K7, by default |

#### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 50 °C |
| Degree of protection  | IP30           |
| Maximum humidity      | 90%            |

#### GENERAL INFORMATION

|               |                             |
|---------------|-----------------------------|
| Type          | 2-door SPC expansion module |
| Compatibility | Vanderbilt Panels           |

#### INPUTS/OUTPUTS

|             |   |
|-------------|---|
| Relay NO/NC | 2 |
| Reader      | 2 |

#### ADDITIONAL FEATURES

|                                 |     |
|---------------------------------|-----|
| Configuration and remote access | Yes |
|---------------------------------|-----|

