



Milesight

Minidome ip camera of 5 megapixels and fix lens

MS-C5375-PD/J

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 4 zones
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	16Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
Main stream	5Mpx / 3Mpx / 1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 25fps)
Sub stream	704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)
Sub stream 2	1080P / 720P / 704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	2592 x 1944
Sensor Size	1/2.8"
Electronic shutter speed	1s to 1/100,000s
Minimum lighting	0.005Lux
Ratio S / N	More than 55dB

LENS

Lens Type	Fix
Focal distance	2.8 mm

VIDEO ANALYSIS

Detection type	Analytical with human/vehicle classification in line/area crossing
Crossing line	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Video Tamper	Yes
Loitering detection	Yes
Classification Human / vehicle	Yes

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	90%

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S, G, T and Q
Management software	Milesight CMS
IP address filter	Yes
Network disconnection	Yes

DISTANCE DORI

Detect	59 m
Observe	23 m
Recognize	12 m
Identify	6 m

GENERAL INFORMATION

Serie	AI Mini Camera Series
Technology	IP
Type of camera	Minidome

NIGHT VISION

technical datasheet

Maximum diaphragm opening	F/1.6
---------------------------	--------------

Angle of View	105°
---------------	-------------

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	------------

Audio compression	G.711 / G.722 / G.726 / AAC
-------------------	------------------------------------

Sampling frequency	8 kHz / 16 kHz / 32 kHz / 48 kHz
--------------------	---

Bit rate	16 Kbps ~ 256 Kbps
----------	---------------------------

POWER CONSUMPTION

Consumption (w)	5.8W
-----------------	-------------

PoE power	Yes
-----------	------------

Type PoE	PoE 802.3af
----------	--------------------

MATERIAL AND DIMENSIONS

Dimensions	96.5 x 108 (Ø) mm
------------	--------------------------

Net weight	600 g
------------	--------------

Weight with packaging	730 g
-----------------------	--------------

AXES

Motion	3-Axis
--------	---------------

Night vision distance	25 m
-----------------------	-------------

Type of night vision	IR
----------------------	-----------

Starlight	Yes
-----------	------------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	--------------------

Storage Systems	NAS / Micro SD / Recorder
-----------------	----------------------------------

ANR (Redundant Recording in SD)	Yes
---------------------------------	------------

