



## 10 ports switch with 8 PoE ports

### VK-SWITCH-1008POE-100

#### POWER CONSUMPTION

Power mode	<b>AC</b>
Voltage	<b>100V ~ 240V</b>
Amperage	<b>2000mA</b>
Standby consumption	<b>5W</b>
Consumption On	<b>100W</b>
Maximum consumption per port (PoE)	<b>30W</b>
Total maximum consumption (PoE)	<b>100W</b>

#### ETHERNET PORTS

POE ports	<b>8</b>
Uplink ports	<b>2</b>
10 / 100 Base-TX	<b>8</b>
POE Ports Speed	<b>10 / 100</b>
Uplink ports speed	<b>10 / 100</b>
Number of Ethernet ports	<b>10</b>

#### MATERIAL AND DIMENSIONS

Installation	<b>Desk / wall</b>
Dimensions	<b>195 x 130 x 40 mm</b>
Material	<b>Metal</b>
Net weight	<b>660 g</b>
Weight with packaging	<b>900 g</b>

#### SYSTEM (SWITCH)

MAC address table	<b>1K</b>
-------------------	-----------

#### AMBIENT

Operating temperature	<b>-20 °C ~ 55 °C</b>
Degree of protection	<b>IP30</b>
Use	<b>Indoor</b>
Maximum humidity	<b>90%</b>
Lightning protection	<b>4KV</b>

#### CHARACTERISTICS (SWITCH)

Data rate supported	<b>2 Gbps</b>
Maximum transmission distance	<b>250 m</b>
Buffer Memory	<b>768K</b>

#### NET STANDARD

IEEE802,3af	<b>Yes</b>
IEEE802,3at	<b>Yes</b>

