

**AJAX****Wired volumetric and glass
break detector****COMBIPROTECT-FIBRA-W****DETECTION**

Detector type	Wired
Installation height	2.4 m
Angle detection	88.5° Horizontal / 80° Vertical
Detection distance	12 m
Detection speed	0,3 m/s ~ 2 m/s
Pets immunity	Up to 20 kg and 50 cm
Sensitive element	Electret microphone
Glass break detection	Sí, hasta 9 metros
Microphone	180° coverage
Detection technology	Volumetric and glass break

TECHNICAL SPECIFICATIONS

Compatibility	Ajax Fibra panels
LED indicators	Yes
Tamper	Yes
Connection type	BUS
Protection against false alarms	Yes, algorithmic analysis
Transmission distance	Up to 2000 m

POWER CONSUMPTION

Power mode	DC (via Hub Hybrid BUS)
Voltage	24V

SENSOR

Type of sensor	PIR and microphone
PIR sensitivity	Selectable LO / MID / HI

MATERIAL AND DIMENSIONS

Dimensions	110 x 65 x 50 mm
Material	Plastic
Net weight	80 g
Weight with packaging	120 g
Color	White

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Degree of protection	IP50
Use	Indoor
Maximum humidity	75%

CERTIFICATION

Grade	2
Normative	EN50131

