



● **detnov**
smoke thermal sensor
DTD-210A-I

AMBIENT

Operating temperature	-10 °C ~ 70 °C
Degree of protection	IP20
Use	Indoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	40 x 102 (Ø) mm
Material	ABS plastic
Net weight	75 g
Weight with packaging	85 g

TECHNICAL SPECIFICATIONS

LED indicators	Yes
Short circuit isolator	Yes
Temperature activation	58°

GENERAL INFORMATION

Type **Smoke thermal sensor**

CONEXIONES (INCENDIO)

Cable **2 x 1.5 mm²**

POWER CONSUMPTION

Power mode	DC
Voltage	22V ~ 38V
Consumption On	11mA

DETECCIÓN (INCENDIO)

Protection area	20 m²
Maximum Mounting height	6 m
Termovelocimétrico	8°C / min





CERTIFICATION

Normative **EN54-5 / EN54-7**

DETECTION

Detection technology **Convenicional termovelocimetrico**



● **detnov**
DTD-210A-I
 Addressable Heat
 Detector with built-in Isolator
 V: 22-38 VDC Iq: 300uA
 doc ref 55321013
 FN 54-5-2017 + A1-2018
 EN 54-17:2005 + AC:2007
 14-0370-CPR-1860
  
 0370

 1572713
 Made by Detnov in Spain (17/11/22)