



## ●detnov incendio central CCD-104

### POWER CONSUMPTION

|                 |                 |
|-----------------|-----------------|
| Power mode      | AC              |
| Voltage         | 90V ~ 264V      |
| Battery support | Entry available |
| Battery model   | 2 x 7.5Ah       |

### AMBIENT

|                       |               |
|-----------------------|---------------|
| Operating temperature | -5 °C ~ 50 °C |
| Degree of protection  | IP30          |
| Use                   | Indoor        |
| Maximum humidity      | 95%           |

### MATERIAL AND DIMENSIONS

|                       |                    |
|-----------------------|--------------------|
| Dimensions            | 439 x 268 x 112 mm |
| Net weight            | 1870 g             |
| Weight with packaging | 2270 g             |

### ZONAS (INCENDIO)

|                                      |    |
|--------------------------------------|----|
| Maximum number of zones              | 4  |
| Maximum number of detectors per zone | 32 |

### ATRIBUTOS

|               |    |
|---------------|----|
| Multilanguage | Sí |
|---------------|----|

### EXITS (FIRE)

|                     |                               |
|---------------------|-------------------------------|
| Fault relay         | 1                             |
| Alarm relay         | 1                             |
| Siren output        | Yes, with delay of 0 ~ 10 min |
| Alarm output 24V DC | Yes                           |

### GENERAL INFORMATION

|                 |              |
|-----------------|--------------|
| Technology      | Convencional |
| Type of Central | Incendio     |

### CERTIFICATION

|           |                           |
|-----------|---------------------------|
| Normative | EN54-2 / EN54-4 / EN54-13 |
|-----------|---------------------------|

### COMUNICACION (INCENDIO)

|          |              |
|----------|--------------|
| Software | Detnov Cloud |
|----------|--------------|

