



**HIKVISION**  
accessories

## Ip video door station with camera

**DS-KD8003-IME1/Flush**

### POWER CONSUMPTION

|                 |                    |
|-----------------|--------------------|
| Power mode      | <b>DC</b>          |
| Voltage         | <b>12V</b>         |
| Consumption (w) | <b>4W</b>          |
| PoE power       | <b>Yes</b>         |
| Type PoE        | <b>PoE 802.3af</b> |

### MATERIAL AND DIMENSIONS

|                        |                            |
|------------------------|----------------------------|
| Installation           | <b>Embed</b>               |
| Dimensions             | <b>98 x 99.8 x 43.9 mm</b> |
| Net weight             | <b>350 g</b>               |
| Weight with packaging  | <b>760 g</b>               |
| Faceplate measurements | <b>134 x 124 x 4 mm</b>    |

### INPUTS/OUTPUTS

|             |          |
|-------------|----------|
| Alarm input | <b>4</b> |
| RS485       | <b>1</b> |
| Door sensor | <b>2</b> |
| Exit button | <b>2</b> |

### CAMERA

|                          |              |
|--------------------------|--------------|
| Resolution               | <b>2 Mpx</b> |
| Horizontal viewing angle | <b>180°</b>  |
| Day / Night              | <b>ICR</b>   |
| Video compression        | <b>H.264</b> |

### CAPACITY

|              |             |
|--------------|-------------|
| Register     | <b>2000</b> |
| Linked gates | <b>500</b>  |

### GENERAL CHARACTERISTICS (VIDEO INTERCOM)

|        |           |
|--------|-----------|
| Tamper | <b>Sí</b> |
|--------|-----------|

### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-40 °C ~ 55 °C</b> |
| Degree of protection  | <b>IP65</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>95%</b>            |

### SYSTEM (RECORDERS)

|                  |                               |
|------------------|-------------------------------|
| Processor        | <b>Embedded MCU Processor</b> |
| Operating system | <b>Embedded LINUX</b>         |
| Flash            | <b>16 MB</b>                  |
| RAM              | <b>256 MB</b>                 |

### AUDIO (VIDEO INTERCOM)

|                   |                                    |
|-------------------|------------------------------------|
| Sound input       | <b>Multidirectional microphone</b> |
| Sound output      | <b>Built-in speaker</b>            |
| Audio compression | <b>G.711u</b>                      |

### GENERAL INFORMATION

|            |                                          |
|------------|------------------------------------------|
| Technology | <b>IP</b>                                |
| Type       | <b>IP Video Door Station with camera</b> |

### NETWORK CHARACTERISTICS (INTERCOM MONITORS)

|                  |                                  |
|------------------|----------------------------------|
| Network protocol | <b>TCP / IP / RSTP</b>           |
| IP connection    | <b>10 / 100Mbps autoadaptive</b> |

### OPENING

|               |                      |
|---------------|----------------------|
| Call elements | <b>Simple button</b> |
|---------------|----------------------|

