



HIKVISION®

Minidome ip camera of 2 megapixels and optical zoom lens

DS-2CD1723G2-LIZSU

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off

DISTANCE DORI

Detect (Open lens)	46 m
Detect (Closed Lens)	140 m
Observe (Open lens)	18 m
Observe (Closed lens)	56 m
Recognize (Open lens)	9 m
Recognize (Closed lens)	28 m
Identify (Open lens)	5 m
Identify (Closed lens)	14 m

AUDIO(CAMERAS)

Built in microphone	Yes
Audio input	1 Input
Audio compression	G.711A / G.711U / G.722.1 / G.726 / AAC-LC / MP2L2 / PCM
Noise filter	SI

NIGHT VISION

Night vision distance	30 m
Type of night vision	Dual light (IR+Luz blanca)
Number of LEDs	3
IR ON/Off	Automatic / Manual
White light	Sí
White light distance	30 m
Wavelength	850 nm
Smart Hybrid Light	Yes (switches from IR to colour with human detection)

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S , G and T
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.9'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.005Lux
Ratio S / N	Más de 52dB

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK08
Use	Indoor-outdoor
Maximum humidity	95%

technical datasheet

Sampling frequency	8kHz / 16kHz
--------------------	--------------

Bit rate	64 Kbps (G.711A / G.711U) / 16 Kbps (G.722.1 / G.726) / 16 ~ 64 Kbps (ACC-LC) / 32 ~ 160 Kbps (MP212)
----------	-------------------------------------------------------------------------------------------------------

Audio output	1
--------------	---

POWER CONSUMPTION

Power mode	DC
------------	----

Voltage	12V
---------	-----

Consumption (w)	9.6W
-----------------	------

Amperage	800mA
----------	-------

PoE power	Yes
-----------	-----

Type PoE	PoE 802.3af
----------	-------------

LENS

Lens Type	Optical zoom
-----------	--------------

Focal distance	2.8 mm ~ 12 mm
----------------	----------------

Maximum diaphragm opening	F/1.6
---------------------------	-------

Angle of View	102.4° ~ 31.2°
---------------	----------------

Filtro IR	Si
-----------	----

GENERAL INFORMATION

Serie	PRO
-------	-----

Technology	IP
------------	----

Type of camera	Minidome
----------------	----------

AXES

Motion	3-Axis
--------	--------

INPUTS/OUTPUTS (CAMERAS)

Alarm	1 Input / 1 Output
-------	--------------------

MATERIAL AND DIMENSIONS

Dimensions	97.6 x 121.5 (Ø) mm
------------	---------------------

Material	Metal and plastic
----------	-------------------

Net weight	540 g
------------	-------

Weight with packaging	740 g
-----------------------	-------

VIDEO ANALYSIS

Detection type	Advanced detection (person/vehicle classification)
----------------	----------------------------------------------------

Motion detection	Yes
------------------	-----

Video Tamper	Yes
--------------	-----

Classification Human / vehicle	Yes
--------------------------------	-----

STORAGE

MicroSD-Card	Hasta 512Gb
--------------	-------------

Storage Systems	NAS / FTP / Micro SD
-----------------	----------------------

SYSTEM (CAMERAS)

Reset button	Yes
--------------	-----

