




## 5 ports cloud switch with 4 PoE ports

DS-3E1105P-EI/M



### REMOTE MANAGEMENT

|                               |                                                         |
|-------------------------------|---------------------------------------------------------|
| Software                      | <b>Hik Partner Pro</b>                                  |
| Reset switch                  | <b>Yes</b>                                              |
| PoE port reset                | <b>Yes</b>                                              |
| Extended mode activation      | <b>Yes, independently per port</b>                      |
| Port speed modification       | <b>Yes</b>                                              |
| Actual power consumption      | <b>Yes, total and per port</b>                          |
| History of peak consumption   | <b>Yes (up to 7 days)</b>                               |
| Real-time traffic information | <b>Yes, by port</b>                                     |
| Connected device information  | <b>Yes, for Hikvision equipment (IP, model, and SN)</b> |
| Automatic topology diagram    | <b>Yes, for connected Hikvision devices</b>             |

### POWER CONSUMPTION

|                                    |              |
|------------------------------------|--------------|
| Power mode                         | <b>DC</b>    |
| Voltage                            | <b>54V</b>   |
| Consumption (w)                    | <b>50W</b>   |
| Amperage                           | <b>920mA</b> |
| Standby consumption                | <b>5W</b>    |
| Maximum consumption per port (PoE) | <b>30W</b>   |
| Total maximum consumption (PoE)    | <b>45W</b>   |

### ETHERNET PORTS

|                          |                                              |
|--------------------------|----------------------------------------------|
| POE ports                | <b>4</b>                                     |
| Uplink ports             | <b>1</b>                                     |
| POE Ports Speed          | <b>10 / 100</b>                              |
| Uplink ports speed       | <b>10 / 100</b>                              |
| Number of Ethernet ports | <b>5</b>                                     |
| Puertos PoE prioritarios | <b>2 (priorizados en caso de congestión)</b> |

### NET STANDARD

|             |            |
|-------------|------------|
| IEEE802,3af | <b>Yes</b> |
| IEEE802,3at | <b>Yes</b> |

### CHARACTERISTICS (SWITCH)

|                               |                        |
|-------------------------------|------------------------|
| Data rate supported           | <b>1.2 Gbps</b>        |
| Packet redirection speed      | <b>0.89 Mpps</b>       |
| VLAN                          | <b>802.1Q</b>          |
| Maximum transmission distance | <b>300 m</b>           |
| Buffer Memory                 | <b>768K</b>            |
| PoE Watchdog                  | <b>Yes</b>             |
| Spanning Tree                 | <b>Yes, STP / RSTP</b> |

### MATERIAL AND DIMENSIONS

|                       |                               |
|-----------------------|-------------------------------|
| Installation          | <b>Desk / wall</b>            |
| Dimensions            | <b>121.1 x 83.1 x 27.6 mm</b> |
| Material              | <b>Metal</b>                  |
| Net weight            | <b>260 g</b>                  |
| Weight with packaging | <b>750 g</b>                  |

### AMBIENT

|                       |                     |
|-----------------------|---------------------|
| Operating temperature | <b>0 °C ~ 40 °C</b> |
| Use                   | <b>Indoor</b>       |
| Maximum humidity      | <b>95%</b>          |
| Lightning protection  | <b>6KV</b>          |

### SYSTEM (SWITCH)

|                   |           |
|-------------------|-----------|
| MAC address table | <b>2K</b> |
|-------------------|-----------|

