HIKVISION accesories

Smart Wi-Fi access point

DS-3WAP522-SI

WI-FI

Wi-Fi standard	**Radio 1: IEEE802.11 a / an / ac / Radio 2: IEEE802.11 b / g / gn**
Frequency range	**Radio 1: 5 GHz / Radio 2: 2.4 GHz**
Broadband channel	**Radio 1: Auto / 20 / 40 / 80 MHz / Radio 2: Auto / 20 / 40 MHz**
Security	**WPA-PSK / WPA2-PSK**
Speed	**Radio 1: 867Mbps / Radio 2: 300Mbps**
Antenna	**2 x Radio 1: 4 dBi / Radio 2: 3 dBi**
Maximum number of clients	**256 (80 recommended)**
Maximum number of SSIDs	**8**

POWER CONSUMPTION

Power mode	**DC**
Voltage	**12V**
Consumption (w)	**11.3W**
Amperage	**1500mA**
PoE power	**Yes**
Type PoE	**PoE 802.3af / PoE+ 802.3at**

TECHNICAL CHARACTERISTICS

LED indicator	**Yes**

MATERIAL AND DIMENSIONS

Dimensions	**35 x 220 (Ø) mm**
Net weight	**370 g**
Weight with packaging	**710 g**

AMBIENT

Operating temperature	**0 °C ~ 40 °C**
Maximum humidity	**95%**

INPUTS/OUTPUTS

RJ45	**1 x 10 / 100 / 1000**