



**HIKVISION**  
intrusion

## BUS input expander DS-PM501Z8T4

### POWER CONSUMPTION

|                     |                |
|---------------------|----------------|
| Power mode          | DC (via BUS)   |
| Voltage             | 12V            |
| Amperage            | 150mA          |
| Standby consumption | 80mA           |
| Power output        | DC 12V / 500mA |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 50 °C |
| Use                   | Indoor         |
| Maximum humidity      | 90%            |

### GENERAL INFORMATION

|               |                  |
|---------------|------------------|
| Serie         | AXPRO            |
| Compatibility | Hikvision panels |

### ZONES

|                         |   |
|-------------------------|---|
| Maximum number of zones | 8 |
| Keyboard areas          | 8 |

### TECHNICAL CHARACTERISTICS

|            |     |
|------------|-----|
| Connection | BUS |
|------------|-----|

### MATERIAL AND DIMENSIONS

|                       |                   |
|-----------------------|-------------------|
| Dimensions            | 155 x 110 x 31 mm |
| Net weight            | 225 g             |
| Weight with packaging | 350 g             |

### CERTIFICATION

|                     |    |
|---------------------|----|
| Grade               | 2  |
| Environmental class | II |

### PROGRAMMABLE OUTPUTS

|                 |   |
|-----------------|---|
| Board           | 4 |
| Maximum of PGMs | 4 |

